

Analytical Results				
Dried Basis Value				

Proximate Analysis		n=	k=	ASTM
% Ash	9.31 ± 0.63	20	2.1	D3174/D7582
% Volatile Matter	35.5 ± 1.3	21	2.1	D3175/D7582
% Fixed Carbon (calculated)	(55.2)	--	--	D3172
% Sulfur	1.11 ± 0.05	40	2.0	D4239
Btu/lb	12726 ± 140	8	2.4	D5865

() – indicates information value only.

References used: Sulfur – SRM 2692c, 1632d, NCS FC28004f, NCS 28010e.
 BTU- Benzoic Acid SRM 39j

**The analytical results above are provided by an accredited reference material manufacturer with a current certification in ISO 17025 and 17034.*

The intended use of this Reference Material (RM) is for the verification of various tests by the above-mentioned methods.

Typical sample size for analytical testing and minimum size is subject to the test method and instrumentation used.

The Period of Validity for this RM is 2 years after opening and should be reviewed 20 years after the date below.

This bottle contains 50g of fine coal powder (-60mesh) to be used per the test method you follow. Keep sealed tightly and store under normal laboratory conditions. The analytical samples should be dried or corrected for moisture as per the test method you are using.

Refer to your test methods and or manufacturer manual for expanded uncertainties, repeatability/reproducibility factors.

For good laboratory practice, we recommend that all reference materials be verified as fit for purpose prior to use. Remedies for any claimed defect in this product will be limited to product replacement or refund of the purchase price. In no event shall Elemental Microanalysis Ltd. be liable for incidental or consequential damages.

Certified on the 10th of October 2023.

Elemental Microanalysis Ltd