

NICKELISED CARBON (50 PERCENT NICKEL)

Page: 1

Compilation date: 16/04/2015

Revision date: 07/02/2022

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: NICKELISED CARBON (50 PERCENT NICKEL)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC21: Laboratory chemicals. PROC15: Use as laboratory reagent

1.3. Details of the supplier of the safety data sheet

Company name: Elemental Microanalysis Ltd

1 Hameldown Road Okehampton

Okehampton

Devon

EX20 1UB

United Kingdom

- Tel: 44(0)183754446
- Fax: 44(0)183754544

Email: info@microanalysis.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 7990 767375

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT RE 1: H372; Carc. 2: H351; Skin Sens. 1: H317

Most important adverse effects: May cause an allergic skin reaction. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.

2.2. Label elements

Label elements:	
Hazard statements:	H317: May cause an allergic skin reaction.
	H351: Suspected of causing cancer.
	H372: Causes damage to organs through prolonged or repeated exposure.
Hazard pictograms:	GHS07: Exclamation mark
	GHS08: Health hazard



NICKELISED CARBON (50 PERCENT NICKEL)

Page: 2

Signal words:	Danger
Precautionary statements:	P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352: IF ON SKIN: Wash with plenty of water.
	P308+P313: IF exposed or concerned: Get medical advice/attention.
	P314: Get medical advice/attention if you feel unwell.
	P362+P364: Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

Other hazards: Danger of serious damage to health by prolonged exposure.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

NICKEL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-111-4	7440-02-0	-	Carc. 2: H351; STOT RE 1: H372; Skin Sens. 1: H317	30-50%

CARBON.

215-609-9	7440-44-0	Substance with a Community	Flam. Sol. 2: H228	30-50%
		workplace exposure limit.		

Section 4: First aid measures

4.1. Description of first aid measures			
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.		
	Consult a doctor. Drench the affected skin with running water for 10 minutes or longer if		
	substance is still on skin.		
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.		
Ingestion:	Wash out mouth with water. Consult a doctor.		
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a		
	doctor.		
4.2. Most important symptom	is and effects, both acute and delayed		
Skin contact:	There may be irritation and redness at the site of contact.		
Eye contact:	There may be irritation and redness. The eyes may water profusely.		
Ingestion:	There may be soreness and redness of the mouth and throat.		
Inhalation:	Exposure may cause coughing or wheezing.		

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

NICKELISED CARBON (50 PERCENT NICKEL)

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust. Evacuate the area immediately.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes or gas.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of dust in the air.

Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

NICKELISED CARBON (50 PERCENT NICKEL)

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

CARBON.

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	3.5mg/m3	3.5mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency. Respiratory
	protective device with particle filter.
Hand protection:	Impermeable gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Granules		
Colour:	Grey		
Odour:	Odourless		
Evaporation rate:	No data available.		
Oxidising:	No data available.		
Solubility in water:	No data available.		
Boiling point/range°C:	No data available.	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	No data available.	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	No data available.	pH:	No data available.
VOC g/l:	No data available.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

NICKELISED CARBON (50 PERCENT NICKEL)

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

NICKEL

IPR	RAT	LD50	250	mg/kg
IVN	MUS	LDLO	50	mg/kg
ORL	RAT	LDLO	5	gm/kg

CARBON.

INTRAVENOUS	MUS	LD50	440	mg/kg
ORAL	RAT	LD50	>8000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Respiratory/skin sensitisation	DRM	Hazardous: calculated
Carcinogenicity		Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

NICKELISED CARBON (50 PERCENT NICKEL)

Page: 6

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

CARBON.

ALGAE	72H ErC50	10000	mg/l
Daphnia magna	96H LC50	5600	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	1000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

NICKELISED CARBON (50 PERCENT NICKEL)

Section 16: Other information

Other information	
Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H228: Flammable solid.
	H317: May cause an allergic skin reaction.
	H351: Suspected of causing cancer.
	H372: Causes damage to organs through prolonged or repeated exposure.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.