

RESIDUAL OIL STANDARD

Page: 1

Compilation date: 11/01/2018

Revision date: 01/02/2022

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: RESIDUAL OIL STANDARD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC21: Laboratory chemicals. PROC15: Use as laboratory reagent

1.3. Details of the supplier of the safety data sheet

Company name: Elemental Microanalysis Ltd

1 Hameldown Road Okehampton

Okehampton

Devon EX20 1UB

Tel: 44(0)183754446 **Fax:** 44(0)183754544

Email: info@microanalysis.co.uk

United Kingdom

1.4. Emergency telephone number

Emergency tel: +44 (0) 7990 767375

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; STOT SE 3: H336; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin

Irrit. 2: H315; Asp. Tox. 1: H304; Carc. 2: H351

Most important adverse effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause

drowsiness or dizziness. Suspected of causing cancer.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS09: Environmental

RESIDUAL OIL STANDARD

Page: 2







Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P362+P364: Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW ROLLING POINT NAPHTHA - LINSPECIFIED - SOLVENT NAPHTHA (PETROLELIM) LIGHT AROM

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.					
EINECS	CAS	PBT / WEL	CLP Classification	Percent	
265-199-0	64742-95-6	-	Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	90-99%	
1,2,4-TRIMET	HYLBENZENE				
202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	30-50%	
XYLENE	·				

CUMENE					
			Acute Tox. 4: H312; Skin Irrit. 2: H315		ı
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332;	1-10%	

202-704-5	98-82-8	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304;	1-10%
			STOT SE 3: H335; Aquatic Chronic 2:	
			H411	

Section 4: First aid measures

RESIDUAL OIL STANDARD

Page: 3

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises. A decontamination shower

should be available on the premises. Immediate medical attention is required. Show

this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water

spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

RESIDUAL OIL STANDARD

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

1,2,4-TRIMETHYLBENZENE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	100 mg/m3	-	-	-

XYLENE

EU	221 mg/m3	442 mg/m3	-	-

CUMENE

EU	100 mg/m3	250 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

RESIDUAL OIL STANDARD

Page: 5

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Aromatic

Evaporation rate: Fast

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: Non-viscous

Boiling point/range°C: 161-171 Melting point/range°C: -26.1

Flammability limits %: lower: 0.9 upper: 6.2

Flash point°C: 46 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: 485 Vapour pressure: 0.269kPa at 20oc

Relative density: No data available. pH: No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

RESIDUAL OIL STANDARD

Page: 6

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	ma/ka
0.1.2	1.0.11		0.00	···g/ ··g

1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

CUMENE

ORL	MUS	LD50	12750	mg/kg
ORL	RAT	LD50	1400	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

RESIDUAL OIL STANDARD

Page: 7

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1268

14.2. UN proper shipping name

Shipping name: * PETROLEUM DISTILLATES, N.O.S. - SOLVENT NAPHTHA (PETROLIUM), LIGHT

AROMATIC

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

RESIDUAL OIL STANDARD

Page: 8

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No

1272/2008.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H350: May cause cancer.

H351: Suspected of causing cancer.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.