

UNIVERSAL COMBUSTION ADDITIVE

Page: 1

Compilation date: 16/04/2015

Revision date: 16/08/2021

Revision No: 13

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: UNIVERSAL COMBUSTION ADDITIVE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC21: Laboratory chemicals. PROC15: Use as laboratory reagent

1.3. Details of the supplier of the safety data sheet

Company name: Elemental Microanalysis Ltd

1 Hameldown Road Okehampton

Okehampton

Devon EX20 1UB

United Kingdom

Tel: 44(0)183754446

Fax: 44(0)183754544

Email: info@microanalysis.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 7990 767375

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: * Acute Tox. 3: H301+H311+H331; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Aquatic

Chronic 3: H412; Skin Irrit. 2: H315; STOT SE 3: H335

Most important adverse effects: Toxic if swallowed, in contact with skin or if inhaled Causes skin irritation. Causes

serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: * H301+H311+H331: Toxic if swallowed, in contact with skin or if inhaled

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

UNIVERSAL COMBUSTION ADDITIVE

Page: 2

Hazard pictograms: GHS06: Skull and crossbones

GHS08: Health hazard





Signal words: Danger

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.

P284: Wear respiratory protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P302+P352: IF ON SKIN: Wash with plenty of water.

P361+P364: Take off immediately all contaminated clothing and wash it before reuse.

P362+P364: Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

Other hazards: Danger of serious damage to health by prolonged exposure.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SILVER VANADATE

EINECS	CAS	PBT / WEL	CLP Classification			
236-820-2	13497-94-4	-	Acute Tox. 3: H301; Acute Tox. 3: H311; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 3: H331; STOT SE 3: H335	30-50%		
SILVER TUNGSTATE						
236-708-3	13465-93-5	_	Skin Irrit, 2: H315: Eve Irrit, 2: H319:	30-50%		

236-708-3	13465-93-5	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	30-50%
			STOT SE 3: H335	

COBALT (II,III) OXIDE.

215-157-2	1308-06-1	-	Aquatic Chronic 3: H412; Resp. Sens.	30-50%
			1: H334	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.Eye contact: Bathe the eye with running water for 15 minutes.Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If

conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If breathing becomes bubbly, have the casualty sit and

provide oxygen if available. Transfer to hospital as soon as possible.

[cont...]

UNIVERSAL COMBUSTION ADDITIVE

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat. There may be shortness of breath due to congestion

of the lungs.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs

causing severe shortness of breath.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: If outside do not approach from downwind. Notify the police and fire brigade

immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do

not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes

or gas.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific

substance. Transfer to a closable, labelled salvage container for disposal by an

appropriate method.

UNIVERSAL COMBUSTION ADDITIVE

Page: 4

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: * Ensure there is exhaust ventilation of the area. Avoid the formation or spread of dust in

the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

COBALT (II,III) OXIDE.

Workplace exposure limits:

Respirable dust:			
9 hour TM/A	15 min STEI		

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	0.1 mg/m3	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is exhaust ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be used in handling. Respiratory protective

device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Powder

Colour: Black

Odour: Odourless

Evaporation rate: No data available.

Oxidising: No data available.

UNIVERSAL COMBUSTION ADDITIVE

Page: 5

Solubility in water: No data available.

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: No data available. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: No data available. pH: No data available.

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

COBALT (II,III) OXIDE.

DERMAL	RAT	LD50	2000	mg/kg
DUST/MIST	RAT	4H LC50	5.06	mg/kg
ORAL	RAT	LD50	5000	mg/kg

UNIVERSAL COMBUSTION ADDITIVE

Page: 6

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 3)	INH DRM ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation OPT		Hazardous: calculated
Respiratory/skin sensitisation	INH	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat. There may be shortness of breath due to congestion

of the lungs.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs

causing severe shortness of breath.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

COBALT (II,III) OXIDE.

ALGAE	72H IC50	88	mg/l
Daphnia magna	48H EC50	136	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

UNIVERSAL COMBUSTION ADDITIVE

Page: 7

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3285

14.2. UN proper shipping name

Shipping name: VANADIUM COMPOUND, N.O.S.

14.3. Transport hazard class(es)

Transport class: 6.1

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

This safety data sheet is prepared in accordance with Commission Regulation (EC) No

1272/2008.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H301: Toxic if swallowed.

UNIVERSAL COMBUSTION ADDITIVE

Page: 8

H301+H311+H331: Toxic if swallowed, in contact with skin or if inhaled

H311: Toxic in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.